



M22 A Basic HPA

*Very good spraying quality and well-balanced fan.
Rugged, for intensive use and large productions.*



Features	Benefits
Polished aluminum body	Easy and quick maintenance
New design of the BA aircap	Spraying quality guaranteed

SPECIFICATIONS

Sprayed materials	Varnishes, lacquers, stains, polyurethanes, two components
Body of the gun	Polished forged aluminum
Max. air feeding pressure (bar)	6
Recommended Trigger air (bar)	2,5 - 3,5
Air consumption (m3/h)	25
Weight (with cup) (g)	1000
Transfer efficiency in % (EN 13966-1)	62
Maximum Fluid Temperature (°C)	50
Nozzle	Inox
Needle	Stainless steel
Wetted parts	Stainless steel, aluminum

FITTINGS

Fitting	Air Inlet	M 1/4" NPS (+ M 1/4" BSP)
	Fluid Inlet	M 3/8" NPS

CONFIGURATION OF THE M22 A Basic HPA

Max Fluid viscosity in CA 4	Projector type	Tip	Fluid output (cc/mn)	Air consumption (m3/h)	Fan width at 20 cm (cm)	Cup	Part number
		Size (mm)					
			-				136.147.200
20 - 40	15 BA2	1,5	220	24	25	SM6	136.147.201
20 - 40	18 BA2	1,8	230	25	26	SM6	136.147.202

SEAL KIT

Designation	Part number
Seal kit	129.130.901