



AIRLESS 40.25 pump - Stainless steel

Ideal for outputs up to 1.5 litre/mn



Features	Benefits
Large diameter suction rod and high compression ratio	Use with a large number of materials
All stainless steel construction	Compatible with water-based products
Simple design , reduced number of spare parts	Easy maintenance

SPECIFICATIONS

Compression ratio	40/1	
Fluid volume per cycle (cm ³)	50	
Number of cycles per litre of products	20	
Fluid Output at 30 cycles/mn (l/mn)	1,5	
Air consumption (m ³ /h) at 30 cycles/mn at 4 bar	21,6	
Free flow rate (L/mn)	3	
Max. air feeding pressure (bar)	6	
Maximum fluid pressure (bar)	240	
Maximum Fluid Temperature (°C)	60	
Sound level (dBA)	77	
Sealing Packings	Upper sealing	Polyfluid + PTFE G
	Lower sealing	GT seal
Wetted parts	Stainless steel	
Weight (kg) - wall-mounted	22	
Height (cm)	80	
Width (cm)	40	
Depth (cm)	28	

FITTINGS

Fitting	Air inlet (valve)	F 3/4" BSP
	Air outlet (option atomization air kit)	M 1/4" NPS
	Fluid Inlet	M 26x125
	Fluid output (filter)	M 1/2" JIC

CONFIGURATION OF THE AIRLESS 40.25 PUMP -STAINLESS STEEL

Set-up	Suction rod	Drain rod	Fluid pressure regulator	Pump output filter	Part number
Wall mounted		-		-	151.775.100
Wall mounted	x	x	x	x	151.775.200
2 arms cart mounted		x		x	151.775.400

ATOMIZATION AIR KIT WITH REGULATOR

Designation	Part number
Atomization air kit with regulator (for MVX200 spray guns)	151.740.200

SEAL KITS

Designation	Part number
-------------	-------------

H25 GT seal kit	144.950.091
H25 GT repair kit	144.950.096
Seal kit for 1000-4 air motor	146.270.991
Repair kit for 1000-4 air motor	146.270.995

KITS FOR AIRLESS 40.25 PUMPS - STAINLESS STEEL

Kit designation	Gun type	Heater	Suction rod	Atomization air regulator	Hoses Length (m)	Pump output filter	Kit part number
40.25 wall mounted	MVX200, VX14 aircap	-	x	x	7.5	x	151.249.420
40.250 wall-mounted, for hot spraying	MVX200, VX14 aircap	x (AD 60)		x	7.5		151.249.430
40.25 wall mounted	M350, with 517 reversible tip	-		-	10		151.249.440