



Airmix® 20.15 Pump - Stainless Steel

The new generation AIRMIX® pump, designed for fluid to semi-fluid materials.



Features	Benefits
All stainless steel construction	Compatible with water-based materials
Large diameter suction rod and high compression ratio	Use with a large number of materials
The gun/pump kits work with a compressor of 2 HP	Reduction of operational costs
Simple design , reduced number of spare parts	Easy maintenance
Compact design	Fits in small working areas

SPECIFICATIONS

Compression ratio	20/1	
Fluid volume per cycle (cm ³)	22	
Number of cycles per litre of products	45	
Fluid Output at 30 cycles/mn (l/mn)	0,66	
Free flow rate (L/mn)	1,32	
Air consumption (m ³ /h) at 30 cycles/mn at 4 bar	4,8	
Max. air feeding pressure (bar)	6	
Maximum fluid pressure (bar)	120	
Maximum Fluid Temperature (°C)	60	
Sound level (dBA)	82	
Sealing Packings	Upper sealing	GT cartridge with polyethylene packing
	Lower sealing	PFA sealing
Weight (kg) - wall-mounted pump w/o rods	9	
Wetted parts	Stainless steel	
Height (cm)	45,7	
Width (cm)	35,6	
Depth (cm)	20,3	

Fitting	Air inlet (valve)	F 3/8 BSP
	Air outlet (atomization air)	M 1/4 NPS
	Fluid Inlet	M 26 x 125
	Fluid Outlet	M 1/2 JIC

CONFIGURATION OF THE AIRMIX® 20.15 PUMPS

Set-up	Suction rod	Drain rod	Atomization air regulator	Fluid pressure regulator	Pump output filter	Part number
Wall mounted	-	-	x	x	-	151.890.150
Wall mounted	x					151.890.060
On one arm cart (1)	x					151.890.250
Portable	x					151.890.200

(1) As an option : 6 litre funnel

6L FUNNEL

Designation	Part number
-------------	-------------

6l funnel (26x125 inlet) - for mounting on one-arm cart	151.890.300
---	--------------------

SEAL KITS

Designation	Part number
H15 Seal kit	144.030.091
H15 Maintenance kit	144.030.092
H15 Rebuilding kit	144.030.093
Repair kit for 700-2 air motor	144.030.090

KIT FOR AIRMIX® 20.15 PUMPS

Kit designation	Gun type	Suction rod	Hoses Length (m)	Filter	Cup	Part number
20.15 wall-mounted pump	MVX 120	x	7,5	-	-	151.260.260