



S3 P HTi

Small HTi gun featuring comfort and precision recommended for precise works and decoration.



Features	Benefits
New ergonomics and body design	The gun is part of the operator's arm who can focus on the application and the spraying movement for an improved quality
Unique aircap design	Unsurpassed finish quality with perfectly balanced fan
E-Z adjust aircap	Allows adjustment without loosening the retaining ring
In-line air valve assembly	Fine adjustment and long lasting components
2 fingers trigger	Improved comfort for more productivity

SPECIFICATIONS

Sprayed materials	Varnishes, lacquers, stains, polyurethanes, two components
Body of the gun	Forged polish aluminum
Max. air feeding pressure (bar)	6
Recommended Trigger air (bar)	3
Air consumption (m3/h)	12
Weight (g)	387
Maximum fluid pressure (bar)	6
Maximum Fluid Temperature (°C)	50
Nozzle	Inox
Needle	Stainless steel
Wetted parts	Stainless steel

FITTINGS

Fitting	Air Inlet	M 1/4" NPS
	Fluid Inlet	M 1/4" NPS

CONFIGURATION OF THE S3 P HTi SPRAY GUN WITH NPS FITTINGS

Max Fluid viscosity in CA 4	Projector type	Tip Size (mm)	Fluid output (cc/mn)	Air consumption (m3/h)	Fan width at 20 cm (cm)	Part number
						135.150.200
14-20 s	08 EPX	0,8	80	12	20	135.150.204
20-30 s	10 EPX	1,0	92		23	135.150.205
30-40 s	12 EPX	1,2	131		24	135.150.206

SEAL KITS

Designation	Part number
Seal kit	129.150.901
Repair kit (includes the seal kit)	129.150.902