

Xcite™ AIRMIX® gun

News Sensations for New Performances

The Xcite™ gun is the result of KREMLIN REXSON experience since 1925. The Xcite™ gun brings an excellent comfort to the operator. Its ultra light trigger, its design, its ergonomics and its swivel fitting reduce the fatigue operator, improve the productivity and stop all risks of RSI (Repetitive strains injuries)

The new Xcite™ gun uses high quality components which ensure a perfect reliability maintaining a high level of performances. The last generation of Airmix® atomization aircap offers **unsurpassed finish quality**.

The sprayer has the ability to significantly vary the pattern without changing the tip while using minimum atomization air and pressure. It's really useful when painting complex shape parts.



Features	Benefits
Ergonomic design and light trigger Product swivel fitting	Reduced fatigue and excellent working conditions for increased productivity
Stainless steel wetted parts	Compatible with water-based materials
Nickel brass air needle	Long service life and good reliability
Large and fine fan width adjustment	Ability to adjust the fan width to the shape of the part to be painted leads to higher efficiency and productivity
Increased atomization quality Increased transfer efficiency	Outstanding spraying quality with reduced overspray
E-Z adjust aircap	Simple using

SPECIFICATIONS

Sprayed materials	Polyurethanes, water-based products, high solids, two-components products, stains, lacquers, varnishes, etc...
Body of the gun	Forged aluminum
Fluid Pressure Range (bar)	20 - 200
Maximum air inlet pressure (bar)	6
Recommended atomization air pressure (bar)	0,8 - 3
Fluid output (l/mn)	Depends on the tip used
Weight (g)	564
Maximum Fluid Temperature (°C)	50
Air consumption (m3/h)	3.2 - 7,5
Wetted parts	Stainless steel, PTFE, carbide
Safety	Trigger lock
Filter (fitted on fluid tube)	#6 - 85 mesh/ 168µ

FITTINGS

Fitting	Air Inlet	M 1/4 NPS
Swivel fitting	Fluid Inlet	M 1/2" JIC

Configuration of the Xcite™ spray gun with fluid swivel fitting

Gun type	Aircap	Tip	Maximum fluid pressure (bar)	Seat	Part number
Xcite™ 120	VX 24 KHVLP	To be ordered separately (see table)	120	Stainless steel	135.720.100
Xcite™ 200			200	Carbide	135.720.200

SEAL KITS

Description	Part number
Seal kit for Xcite™ gun	129.729.901
Repair kit for Xcite™ gun (seal kit included)	129.729.903

KITS FOR AIRMIX® MVX SPRAY GUNS WITH SWIVEL FITTINGS

Description	Aircap	Tip	Diameter		Hoses Length (m)	Kit part number
	Type		Fluid hose (mm)	Conductive air hose (mm)		
Xcite™ 120	VX 24 K HVLP	To be ordered separately (see table)	4,8	7	7,5	151.260.960
Xcite™ 200	VX 24 K HVLP	To be ordered separately (see table)	4,8	7	7,5	151.260.961

Xcite™ Kits with pumps

Kit designation	Gun type	Aircap	Tip	Hoses Length (m)	Suction rod	AD60 Heater	Filter pump outlet	Kit part number
Wall-mounted 10.14 Kit	Xcite™ 120	VX 24 K HVLP	To be ordered separately (see table)	7,5	x	-	-	151.260.962
Portable 10.14 Kit								151.260.963
Portable 10.14 kit with funnel								151.260.964
Wall-mounted 20.15 Kit	Xcite™ 120	VX 24 K HVLP	To be ordered separately (see table)	7,5	x	-	-	151.260.965
Wall-mounted 20.15F Kit								151.260.971
Wall-mounted 20.25 Kit	Xcite™ 120	VX 24 K HVLP	To be ordered separately (see table)	7,5	x	-	x	151.260.966
Wall-mounted stainless steel 17.A2 Kit	Xcite™ 120	VX 24 K HVLP	To be ordered separately (see table)	7,5	x	-	x	151.260.967
Wall-mounted 40.25 Kit	Xcite™ 200	VX 24 K HVLP	To be ordered separately (see table)	7,5	x	-	x	151.260.968
Hot spraying wall-mounted 40.25 Kit						x		151.260.969
Wall-mounted stainless steel 34A2 Kit	Xcite™200	VX 24 K HVLP	To be ordered separately (see table)	7,5	x	-	x	151.260.970